CONTRACT No. NONR 839(23)
PROJECT No. NR 064-433

HEAT TRANSFER AND TEMPERATURE DISTRIBUTION IN A HEMISPHERICAL NOSE CONE IN HYPERSONIC FLOW

by

S. V. Nardo and Ronald W. Sadler

POLYTECHNIC INSTITUTE OF BROOKLYN

DEPARTMENT
of
AEROSPACE ENGINEERING
and
APPLIED MECHANICS

JANUARY 1962

PIBAL REPORT NO. 597

Contract No. Nonr 839(23)
Project No. NR 064-433

HEAT TRANSFER AND TEMPERATURE DISTRIBUTION IN A HEMISPHERICAL NOSE CONE IN HYPERSONIC FLOW

by

S. V. Nardo and Ronald W. Sadler

Polytechnic Institute of Brooklyn
Department of
Aerospace Engineering and Applied Mechanics

January 1962

PIBAL Report No. 597

TABLE OF CONTENTS

1. ABSTRACT

The heat transfer to a hemispherical nose cone subjected to hypersonic flow conditions is calculated for three Reynolds Numbers. The theory is compared with the results of test runs at these Reynolds Numbers on a stainless steel hemisphere in the Polytechnic hypersonic tunnel facility. Except for the region of highest (theoretical) heat input, the comparison is good.

Using the theoretical heat transfer results in conjunction with the one-dimensional transient heat conduction solution through a spherical shell element, temperature histories are obtained at selected points in the interior of the hemispherical nose cone. A comparison with experimental data shows a satisfactory agreement.

It is concluded that the theoretical heat transfer values used in conjunction with the one-dimensional transient heat conduction solution through a spherical shell element, are adequate for predicting the temperature distribution within the hemispherical nose cone. The restrictions are to flows with a Reynolds Number range of from one to five million, stagnation temperatures less than 4000^{o}R, and pressure distributions similar to that given in this report.

2. SYMBOLS

(B)	buried thermocouple, located midway between heated and insulated (inner) surfaces
C_f	local skin friction coefficient
f''	Blasius non-dimensional friction factor
h	enthalpy
(H)	thermocouple located on heated surface
(I)	thermocouple located on insulated surface
k	thermal conductivity
N_R	Reynolds number, $\rho_{s_e} (h_{s_e})^{1/2} R_o/\mu_{s_e}$
$\tilde{N}_R$	$N_R \varphi_{s_e}^{1/2}$
N_{R_θ}	Reynolds number based on momentum thickness, $\rho_e u_e \theta/\mu_e$
N_u	Nusselt number, $q_w R_o/(T_{s_e} - T_w) k_{s_e}$
P	pressure
P_r	Prandtl number
q	heat transfer per unit area per unit time
r	perpendicular distance from surface to centerline of hemisphere
$\bar{r}$	r/R_o
R_o	external nose radius of hemisphere
s	distance along surface measured from the stagnation point along a meridian
$\bar{s}$	s/R_o
T	temperature
$\bar{T}$	$(T_s - T)/(T_s - T_i)$

u	local velocity at edge of boundary layer
$\bar{u}$	$u/(h_{s_e})^{1/2}$
β	pressure gradient parameter
δ^*	boundary layer displacement thickness
φ_{s_e}	$p_s/\rho_{s_e} h_{s_e}$
θ	momentum thickness
μ	viscosity coefficient
$\bar{\mu}$	μ_e/μ_{s_e}
ρ	mass density
$\bar{\rho}$	ρ_e/ρ_{s_e}
τ	shear stress

Subscripts

aw	adiabatic wall
e	conditions external to the boundary layer
i	initial conditions
s	stagnation conditions
w	wall conditions

3. INTRODUCTION

This report is one of a series dealing with the general problem of temperatures, deformations, and material changes of a hemispherical configuration in a hypersonic flow environment. The principal purpose of this report is to present a simple method for predicting the temperature distribution within the hemispherical body under certain restricted hypersonic flow conditions. A reasonably accurate knowledge of the temperature distribution will be necessary for subsequent theoretical studies of stresses and deformations, and for the interpretation of experimental results.

First, a theoretical analysis is made of the heat transfer to a hemispherical body under hypersonic conditions for laminar, turbulent, and transition boundary layer regions. The results are compared with experimental heat transfer data obtained on a hemispherical nose cone configuration in the Polytechnic hypersonic facility.

Except for the region of highest heat input, the agreement between theory and experiment is sufficiently satisfactory to suggest the following simplification in the temperature distribution estimation within the hemisphere. The local theoretical heat transfer coefficient is used in conjunction with the transient one-dimensional heat conduction solution for spherical shell elements. Temperature-time histories at selected points in the interior are compared with available test data and the agreement is

found to be quite satisfactory for purposes of future estimation of temperatures on similar models which are not equipped with thermocouple instrumentation.

Future hemispherical nose cone models of various thicknesses, but of similar external configuration will be instrumented only on the inner, or insulated surface. Thus, if the method of estimating temperatures presented in this report is reasonably accurate, these predictions can be used to obtain the physical properties of materials from data available on the variation of these properties with temperature, to calculate thermal stresses, and for any purpose requiring a knowledge of the temperature to make calculations and to evaluate experimental data.

4. THEORETICAL HEAT TRANSFER CALCULATIONS

The heat transfer to a hemispherical configuration under hypersonic conditions was calculated for three values of the Reynolds Number, $\tilde{N}_R$: 0.97×10^6, 3.3×10^6 and 5.1×10^6. The Reynolds Numbers were chosen to coincide with the values at which hypersonic tunnel tests had previously been run on a stainless steel hemisphere. This stainless steel model was specifically designed to obtain experimental values of the heat and load input. Complete data are reported in Ref. [1], but a brief description of the model and tests are given in Section 5.

The technique for predicting the laminar heat transfer under the above conditions may readily be obtained from Ref. [2], [3], and [4]. In Ref. [2], Lees provides the most convenient method for estimating the laminar heat transfer under hypersonic conditions. It involves the assumption of a constant value of pressure gradient parameter, β, in the transformed coordinate system; a ratio of wall to stagnation enthalpy, small compared to unity, and a linear dependence of viscosity on temperature ($\rho_e \mu_e = \rho_w \mu_w$). There results a simple numerical evaluation of an integral of external flow properties and radius to determine the heat transfer distribution.

In terms of the variables used here, the theory of Lees gives

$$\frac{N_u}{\tilde{N}_R^{1/2}} = (0.353)\, P_r^{\frac{1}{3}} (\varphi_{s_e})^{-\frac{1}{4}} \cdot \frac{\bar{\rho}\,\bar{u}\,\bar{\mu}\,\bar{r}}{\left[\int_0^{\bar{s}} \bar{\rho}\,\bar{u}\,\bar{\mu}\,\bar{r}^2\, d\bar{s}\right]^{\frac{1}{2}}}$$

The limiting process for obtaining the stagnation point value from the above equation leads to the axially symmetric stagnation point heat transfer ($\bar{\rho} \longrightarrow 1$, $\bar{u} \longrightarrow \bar{\beta}\,\bar{s}$ etc.). This gives

$$\frac{N_u}{\tilde{N}_R^{1/2}} = (0.706)\, P_r^{1/3} (\varphi_{s_e})^{-\frac{1}{4}} (\bar{\beta})^{1/2}$$

where

$$\bar{\beta} = (d\bar{u}/d\bar{s}) \quad \text{at} \quad \bar{s} = 0 \,.$$

The technique involving the determination of the transitional and turbulent heat transfer requires the determination of the transition point on the model. N_{R_θ} values of 200 and 300 were chosen for this model. These transition Reynolds Numbers are based on experimental results performed by various investigators.

Before starting the analysis of the turbulent boundary layer, it is necessary to evaluate the laminar coefficient of wall friction at the transitional point.

By definition, the wall friction coefficient is:

$$C_f/2 = \tau_w/(\rho_e u_e^2) .$$

Through Lees transformation,

$$C_f/2 = \frac{\mu_e R_o}{(2\bar{s})^{1/2}} f_w'' ,$$

which may be written as

$$C_f/2 = 0.22/N_{R_\theta} .$$

To evaluate the wall friction coefficient in the transitional and fully turbulent flow regimes, the friction law developed in Ref. [5] was adopted.

$$C_f/2 = \bar{\mu}\left[\frac{0.013}{N_{R_\theta}^{1/4}} - \frac{B}{N_{R_\theta}^{n}}\right]$$

This law is similar in form to that developed by Persh, Ref. [6]. The value of n was taken as 1, as suggested in Ref. [9].

The constant B of this law is evaluated from the laminar flow such that the friction coefficient $C_f/2$ remains continuous at the laminar to turbulent transition point.

$$B = \left[N_{R_\theta}^{n}\left(\frac{0.013}{N_{R_\theta}^{1/4}} - \frac{C_f}{2}\frac{\mu_{s_\theta}}{\mu_e}\right)\right]_{trans.}$$

In order to obtain the heat transfer, a stepwise solution of the boundary layer momentum equation is obtained through the use of boundary layer form factors which are based on a correlation of incompressible data.

$$\frac{d\theta}{ds} = (C_f/2) - \theta\left[\frac{(\delta^*/\theta) + 2}{u_e}\frac{du_e}{ds} + \frac{1}{\rho_e}\frac{d\rho_e}{ds} + \frac{1}{r}\frac{dr}{ds}\right]$$

In this work, following the suggestion of Ref. [5], the form factor was taken as:

$$H_e = (\delta^*/\theta) \cong -1 .$$

The heat transfer is calculated from

$$q_w = P_r^{-(2/3)}(h_{aw} - h_w)\,\rho_e\, u_e (C_f/2)$$

and finally

$$N_u = P_r^{1/3}\left(\frac{h_{aw} - h_w}{h_{s_e} - h_w}\right)\frac{\overline{\rho}\,\overline{u}}{\varphi_{s_e}^{1/2}}\,(C_f/2)\,\tilde{N}_R .$$

The theoretical distribution of heat transfer along a meridian for a laminar boundary layer is shown in Fig. 1. The heat transfer parameter $(N_u/N_R^{\frac{1}{2}})$ correlates the heat transfer for any value of the Reynolds Number. In the transition and turbulent boundary layer range, however, the calculations were made

for three specific values of the Reynolds Number. Fig. 2 presents the results of calculations based on a transition-turbulent boundary layer for Reynolds Numbers of 0.97×10^6, 3.3×10^6 and 5.1×10^6. Transition from laminar boundary layer is assumed to occur at a Reynolds Number based on a momentum thickness (N_{R_θ}) of 250. The heat transfer parameter $N_u/\tilde{N}_R^{4/5}$ is plotted against distance along the meridian from the stagnation point. In Fig. 3, the same calculations, based on a transition value of $N_{R_\theta} = 300$ are graphically presented.

5. COMPARISON WITH EXPERIMENTS

In Ref. [1], the results of 6 test runs at simulated hypersonic speeds on a hemispherical model were reported in both graphical and tabular form. The model was fabricated of Type 304 stainless steel, had a 7-3/4 inch outside diameter and one-inch wall. It was extensively instrumented with pressure taps and thermocouples. The principal mission of these tests was to obtain basic data on both the aerodynamic and thermal loads. Aerodynamic load data were presented in Ref. [1] and are also shown in Fig. 4. (This pressure distribution was used in calculating the theoretical heat transfer). The procedure for obtaining the thermal input, based on the thermocouple temperature-time histories, is outlined below.

The hemispherical model was instrumented with a total of 40 thermocouples, as shown in Fig. 5. Thirteen of these thermocouples were specially constructed one-dimensional plugs for heat transfer work. This instrument was first described in Ref. [7], and further discussed in Ref. [1]. A sketch of a typical thermocouple plug is shown in Fig. 6. The principal virtue of these plugs is the relative ease with which the heat input could be deduced from the temperature-time history of the thermocouple on the heated surface of the model. The remaining thermocouple installations were "standard", and were disposed on the outer and inner surfaces of the model as well as at interior

points. Sketches of a "standard" heated surface thermocouple and a buried thermocouple installation are shown in Figs. 7 and 8.

The experimental values of the heat transfer were deduced from the one-dimensional plug temperature-time histories, and from similar data from the standard thermocouple installations on the outer (heated) surface of the model. In the case of the one-dimensional plugs, the heat conduction equations for the transient one-dimensional flow of heat through a finite slab were solved for the heat input q_w on the heated side of the slab as a function of time. The other side of the slab was considered to be insulated. The plug temperature-time history was used as a boundary condition. Except for the first few seconds, the values of q_w thus calculated, resulted in an essentially constant value of the Nusselt Number. The time average of the almost constant value of the Nusselt Number was used as the experimental value presented in this report.

In obtaining the experimental heat transfer from the standard heated surface thermocouples, use was made of the transient heat conduction solution for the flow of heat through a spherical shell element, one-dimensional, outside surface heated, inside surface insulated, Ref. [8]. For the geometry parameter corresponding to the tested model, temperature-time plots were carefully drawn for constant values of the heat transfer coefficient. When the experimental temperature-time history was superimposed upon this set of curves, the heat transfer coefficient

could easily be interpolated at several points and the results averaged. Again, these heat transfer coefficient values were essentially constant after the first few seconds of the test run.

A comparison of the experimental values of the heat transfer thus deduced with the theoretical values is shown in Figs. 9, 10 and 11.

In Fig. 9, for example, the theoretical curves are given in the form of Nusselt Number versus distance along the meridian from the stagnation point for a value of $\tilde{N}_R = 0.97 \times 10^6$. These curves are easily obtained from the basic data presented in Figs. 1, 2 and 3. Note, from Table 1, that a value of $\tilde{N}_R = 0.97 \times 10^6$ corresponds closely to test runs 1 and 2, and hence experimental data from these runs are shown. The experimental data deduced from the one-dimensional plugs are consistently higher than those data deduced from the standard surface thermocouple installations. Near the stagnation point, there is a discrepancy of up to 25% between theory and experiment, but there is an improvement with higher values of $\bar{s}$. Unfortunately, it is not altogether certain whether transition occurs at the lowest Reynolds Number, 0.97×10^6 (Fig. 9); but if transition does occur it would be at a value of $\bar{s} > 0.9$.

Fig. 10 shows the comparison between theory and experiment for $\tilde{N}_R = 3.3 \times 10^6$, corresponding to conditions of test runs 3 and 4. A similar presentation for $\tilde{N}_R = 5.1 \times 10^6$, corresponding to test run 5 is shown in Fig. 11. Once again it can be noted that experimental heat transfer values from the thermocouple plugs are usually higher than the heat transfer values deduced from the standard surface thermocouple data. In Figs. 10 and 11 there is

no question of transition of the boundary layer from laminar to turbulent. Additional data in the region of highest heat transfer would have been desirable. Several of the instruments in this area, however, were damaged during the installation of the model into the wind tunnel and during the course of the test runs.

On the basis of the comparisons of Figs. 9, 10 and 11, it was decided to take the heat transfer results calculated for the laminar case and for N_{R_θ} = 300 and use the heat conduction equations through a spherical element to predict the temperatures within the hemispherical model.

6. TEMPERATURE DISTRIBUTION

The temperature distribution within the hemispherical model was calculated by utilizing the heat conduction solutions for the transient one-dimensional flow of heat in a spherical shell element, Ref. [8]. For a given $\bar{\varepsilon}$ and $\tilde{N}_R$, the heat transfer coefficient was taken from Figs. 9, 10, or 11. The inner surface was assumed to be insulated. Temperature-time histories could therefore be obtained at any point within the model, for any of the three Reynolds Number ranges for which the theoretical heat transfer calculations were made.

In the six test runs of Ref. [1], thermocouples were buried at various points within the body (see Fig. 5) and on the inner surface. Therefore, the points selected for computing the temperature-time histories by the above method, included points at which thermocouples were physically located on the model. The obvious purpose was to obtain a comparison between the experimental and the calculated temperature-time histories.

The results of this comparison are presented in Figs. 12 and 13, corresponding to the lowest and highest Reynolds Number, respectively. An examination of these temperature-time histories reveals that the calculated temperatures are usually higher than those measured during the test. ($\bar{T}$ is defined in such a manner that it will decrease with increasing temperature.) Maximum deviation from the experimentally determined temperatures occurs at

$\bar{s} = 1.4$; 6.3% difference at $\tilde{N}_R = 0.97 \times 10^6$, and 13.4% difference at $\tilde{N}_R = 5.1 \times 10^6$. At the points of highest heat transfer, the percentage error was somewhat less. For example, for runs 1 and 2, $\tilde{N}_R = 0.97 \times 10^6$, thermocouples 24 and 36 at $\bar{s} = 0.698$ gave temperature-time histories for which the maximum deviation from the calculated temperature-time history was approximately 2.5%. At the highest Reynolds Number, the comparable error at the same location was 10%. It may be noted that while the maximum percentage error occurs at the region of highest theoretical heat input, the maximum percentage errors in temperature occurred elsewhere.

The agreement between the experimental and calculated temperature-time histories is good when one considers that the calculated temperatures are based on a one-dimensional heat conduction solution. The fact that the calculated values of the temperature are almost always higher than the experimental values is not wholly unexpected inasmuch as the calculated heat transfer results are generally higher than those deduced from the plugs and surface thermocouples.

7. CONCLUSIONS

On the basis of the comparison between theory and experiment of heat transfer and temperature distribution presented in this report, it is concluded that the simplified method used to predict temperatures within a hemispherical nose cone in a hypersonic flow is satisfactory. The restriction must be made to flows in the Reynolds Number range of from 1×10^6 to 5×10^6, and to stagnation temperatures less than $4000^{\circ}R$. In order to apply the method it is first necessary to calculate the theoretical heat transfer for the appropriate Reynolds Number. Using the local values of the heat transfer, in conjunction with the transient, one-dimensional heat conduction solution through a spherical shell element, yields the temperature-time history at any point within the body.

8. ACKNOWLEDGEMENT

The authors gratefully acknowledge the assistance of Professors Libby, Cresci, Zakkay and Mr. Economos, of the Aerodynamics Laboratory staff, for their assistance in obtaining the theoretical heat transfer values presented in this report.

Many thanks are also due Messrs. Brown and Parisse for their assistance with the calculations and preparation of the illustrations.

REFERENCES

1. Nardo, S.V., Boccio, J.L., Erickson, B. and Kempner, J.: Experimental Temperature Distribution in a Hemispherical Nose Cone in Hypersonic Flow, PIBAL Report No. 494, June 1959.
2. Lees, L.: Laminar Heat Transfer Over Blunt-Nosed Bodies at Hypersonic Flight Speeds, Jet Propulsion, Vol. 26, pp. 259-269, April 1956.
3. Fay, J.A., Riddell, F.R. and Kemp, N.J.: Stagnation Point Heat Transfer in Dissociated Air Flow, Jet Propulsion, Vol. 27, No. 6 pp. 672-674, June 1957.
4. Cohen, Clarence B. and Reshotko, Eli: Similar Solutions for the Compressible Laminar Boundary Layer with Heat Transfer and Pressure Gradient, NACA Report 1293, 1956.
5. Cresci, R.J., MacKenzie, D.A. and Libby, P.A.: An Investigation of Laminar, Transitional and Turbulent Heat Transfer on Blunt-Nosed Bodies in Hypersonic Flow, Journal of the Aerospace Sciences, Vol. 27, No. 6, pp. 401-414, June 1960.
6. Persh, J.: A Procedure for Calculating the Boundary Layer Development in the Region of Transition from Laminar to Turbulent Flow, U.S.N.O.L. NAVORD Report 4438, March 1957.
7. Ferri, A. and Libby, P.A.: A New Technique for Investigating Heat Transfer and Surface Phenomena Under HYpersonic Flow Conditions, Journal of the Aerospace Sciences, Vol. 24, No. 6, pp. 464-465, June 1957.

8. Smithson, R.E. and Thome, C.J.: U. S. Naval Ordnance Test Station NAVORD Report 5562, Part 6, NOTS 2088, September 1958.

9. Economos, C. and Libby, P.A.: A Note on Transitional Heat Transfer Under Hypersonic Conditions, Reader's Forum, Journal of the Aerospace Sciences, Vol. 29, No. 1, pp. 101-102, January 1962.

TABLE I

STAGNATION DATA

Run	T_s (^oR)	p_s (psia)	$\rho_s \times 10^3$ ($\frac{lb\ sec^2}{ft^4}$)	$h_s \times 10^{-6}$ ($\frac{ft^2}{sec^2}$)	$\mu_s \times 10^6$ ($\frac{lb\ sec}{ft^2}$)	$N_R \times 10^{-6}$	$\tilde{N}_R \times 10^{-6}$	$\frac{\mu_s C_p}{k_s}$	$k_s \times 10^3$ ($\frac{Btu\ in}{ft^2\ sec\ ^oF}$)
1	1285	21.4	1.398	8.27	.705	1.78	.953	.680	.103
2	1283	22.4	1.463	8.27	.705	1.87	1.00	.689	.102
3	1418	83.8	4.959	9.32	.750	6.23	3.34	.696	.109
4	1462	84.6	4.856	9.65	.763	6.08	3.26	.695	.112
5	1656	152	7.702	11.1	.822	9.51	5.09	.701	.121
6	1865	152	6.839	12.8	.885	8.34	4.47	.713	.132



FIG. 1 THEORETICAL DISTRIBUTION OF HEAT TRANSFER ALONG MERIDIAN OF HEMISPHERE LAMINAR BOUNDARY LAYER



FIG. 2 THEORETICAL DISTRIBUTION OF HEAT TRANSFER ALONG MERIDIAN OF HEMISPHERE TRANSITION - TURBULENT BOUNDARY LAYER $N_{R_0} = 250$



FIG. 3 THEORETICAL DISTRIBUTION OF HEAT TRANSFER ALONG MERIDIAN OF HEMISPHERE
TRANSITION - TURBULENT BOUNDARY LAYER
N_{R_0} = 300



FIG. 4 PRESSURE DISTRIBUTION ON HEMISPHERICAL NOSE CONE
(FROM TEST DATA OF REF. 1)



FIG. 5 LOCATION OF INSTRUMENTATION
MODEL NO. 1
(REF. 1)



FIG. 7 TYPICAL HEATED SURFACE THERMOCOUPLE ASSEMBLY (REF. 1)



FIG. 6 TYPICAL ONE-DIMENSIONAL THERMOCOUPLE PLUG INSTALLATION (REF. 1)



FIG. 8 TYPICAL BURIED THERMOCOUPLE ASSEMBLY (REF. 1)



FIG. 9 VARIATION OF NUSSELT NUMBER ALONG MERIDIAN OF HEMISPHERE $\tilde{N}_R = 0.97 \times 10^6$ - RUNS 1 AND 2



FIG. 10 VARIATION OF NUSSELT NUMBER ALONG MERIDIAN OF HEMISPHERE $\tilde{N}_R = 3.3 \times 10^6$ - RUNS 3 AND 4



FIG. 11 VARIATION OF NUSSELT NUMBER ALONG MERIDIAN OF HEMISPHERE
$\tilde{N}_R = 5.1 \times 10^6$ - RUN 5



FIG. 12 COMPARISON OF EXPERIME..TAL AND CALCULATED TEMPERATURE-TIME HISTORIES
RUNS 1 AND 2
$N_R = 0.97 \times 10^6$

(H) HEATED SURFACE
(B) BURIED
(I) INSULATED SURFACE
——— THEORETICAL
- -o- -o- - EXPERIMENTAL



FIG. 13 COMPARISON OF EXPERIMENTAL AND CALCULATED TEMPERATURE - TIME HISTORIES
RUN 5 - N_R = 5.1 X 10^6

(H) HEATED SURFACE
(B) BURIED
(I) INSULATED SURFACE

——— THEORETICAL

- -o- -o- - EXPERIMENTAL

DISTRIBUTION LIST FOR UNCLASSIFIED TECHNICAL REPORTS ISSUED UNDER CONTRACT NONR 839(23), TASK NR 064-433

Chief of Naval Research
Department of the Navy
Washington 25, D.C.
Attn: Code 438 (1)
Code 439 (1)

Commanding Officer
Branch Office
Office of Naval Research
495 Summer Street
Boston 10, Massachusetts (1)

Commanding Officer
Office of Naval Research
Branch Office
John Crerar Library Building
86 E. Randolph Street
Chicago 1, Illinois (1)

Commanding Officer
Office of Naval Research
346 Broadway
New York 13, New York (1)

Commanding Officer
Office of Naval Research
Branch Office
1030 E. Green Street
Pasadena, California (1)

Commanding Officer
Office of Naval Research
Branch Officer
1000 Geary Street
San Francisco, California (1)

Commanding Officer
Office of Naval Research
Navy No. 100, Fleet Post Office
New York, New York (25)

Director
Naval Research Laboratory
Washington 25, D. C.
Attn: Tech. Info. Officer (6)
Code 6200 (1)
Code 6205 (1)
Code 6250 (1)
Code 6260 (1)

Armed Services Tech. Info. Agency
Arlington Hall Station
Arlington 12, Virginia (10)

Office of Technical Services
Department of Commerce
Washington 25, D. C. (1)

Office of the Secretary of Defense
Research & Development Division
The Pentagon
Washington 25, D. C.
Attn: Technical Library (1)

Chief
Defense Atomic Support Agency
Washington 25, D. C.
Attn: Document Lib. Br. (1)

Office of the Secretary of the Army
The Pentagon
Washington 25, D. C.
Attn: ; Army Library (1)

Chief of Staff
Department of the Army
Washington 25, D. C.
Attn: Develop. Br. (R & D Div.) (1)
Research Br. (R & D Div.) (1)
Spec. Weaps. Br.
(R & D. .) (1)

Office of the Chief of Engineers
Department of the Army
Washington 25, D. C.
Attn: ENG-EB Prot. Const. Br., Eng. Div. Mil. Const. (1)
ENG-HL Lib. Br. Adm. Ser. Div. (1)
ENG-EA Struc. Br., Eng. Div. Mil. Const. (1)
ENG-NB Special Eng. Br. Eng. R & D Div.) (1)
ENG-WD Planning Div. Civ. Works (1)

Commanding Officer
Engineer Research Development Lab.
Fort Belvoir, Virginia (1)

Office of the Chief of Ordnance
Department of the Army
Washington 25, D. C.
Attn: Research & Materials Br. (Ord. R & D Div.) (1)

Commanding Officer
Watertown Arsenal
Watertown, Massachusetts
Attn: Laboratory Division (1)

Commanding Officer
Frankford Arsenal
Bridesburg Station
Philadelphia 37, Pennsylvania
Attn: Laboratory Division (1)

Office of Ordnance Researc h
2127 Myrtle Drive
Duke Station
Durham, North Carolina
Attn: Div. of Eng. Sciences (1)

Commanding Officer
U.S. Army Signal Res.& Dev. Lab.
SIGFM/EL-G
Fort Monmouth, New Jersey (1)

Chief of Naval Operations
Department of the Navy
Washington 25, D. C.
Attn: Op 37 (1)

Commandant Marine Corps
Headquarters, U.S. Marine Corps
Washington 25, D. C. (1)

Chief, Bureau of Ships
Department of the Navy
Washington 25, D. C.
Attn: Code 312 (2)
Code 376 (1)
Code 377 (1)
Code 420 (1)
Code 423 (2)
Code 442 (2)

Chief, Bureau of Aeronautics
Department of the Navy
Washington 25, D. C.
Attn: AE-4 (1)
AV-34 (1)
AD (1)
AD-2 (1)
RS-7 (1)
RS-8 (1)
SI (1)
TS-42 (1)

Chief, Bureau of Ordnance
Department of the Navy
Washington 25, D.C.
Attn: Ad 3 (1)
Re (1)
Res (1)
Reu (1)
ReS5 (1)
ReS1 (1)
Ren (1)

Special Projects Office
Bureau of Ordnance
Department of the Navy
Washington 25, D.C.
Attn: Missile Branch (2)

Chief, Bureau of Yards & Docks
Department of the Navy
Washington 25, D.C.
Attn: Code D-202 (1)
Code D-202.3 (1)
Code D-220 (1)
Code D-222 (1)
Code D-410C (1)
Code D-440 (1)
Code D-500 (1)

Commanding Officer & Director
David Taylor Model Basin
Washington 7, D. C.
Attn: Code 140 (1)
Code 600 (1)
Code 700 (1)
Code 720 (1)
Code 725 (1)
Code 731 (1)
Code 740 (2)

Commander
U.S. Naval Ordnance Laboratory
White Oak, Maryland
Attn: Technical Library (2)
Technical Evaluation Dep.(1)

Director
Materials Laboratory
New York Naval Shipyard
Brooklyn 1, New York (1)

Commanding Officer & Director
U.S. Naval Electronics Lab.
San Diego 52, California (1)

Officer-in-Charge
Naval Civil Engineering Research
and Evaluation Laboratory
U.S. Naval Construction
Battalion Center
Port Hueneme, California (2)

Director
Naval Air Experimental Station
Naval Air Material Center
Naval Base
Philadelphia 12, Pennsylvania
Attn: Materials Laboratory (1)
Structures Laboratory (1)

Officer-in-Charge
Underwater Explosion Research Div.
Norfolk Naval Shipyard
Portsmouth, Virginia
Attn: Dr. A.H. Keil (2)

Commander
U.S. Naval Proving Grounds
Dahlgren, Virginia (1)

Commander
Naval Ordnance Test Station
Inyokern, China Lake, California
Attn: Physics Division (1)
Mechanics Branch (1)

Commander
Naval Ordnance Test Station
Underwater Ordnance Division
3202 E. Foothill Boulevard
Pasadena 8, California
Attn: Structures Division (1)

Commanding Officer & Director
Naval Engineering Experiment Station
Anapolis, Maryland

Superintendent
Naval Post Graduate School
Monterey, California (1)

Commandant
Marine Corps Schools
Quantico, Virginia
Attn: Director, Marine Corps
Development Division (1)

Commanding General
U.S. Air Force
Washington 25, D.C.
Attn: Research & Devel. Div. (1)

Commander
Air Material Command
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: MCREX-B (1)
Structures Division (1)

Commander
U.S. Air Force Institute of Tech.
Wright-Patterson Air Force Base
Dayton, Ohio=
Attn: Chief, Applied Mechanics Group (1)

Director of Intelligence
Headquarters, U.S. Air Force
Washington 25, D.C.
Attn: P.V. Branch
(Air Targets Division)(1)

Commander
Air Force Office of Scientific Res.
Washington 25, D.C.
Attn: Mechanics Division (1)

U.S. Atomic Energy Commission
Washington 25, D.C.
Attn: Director of Research (2)

Director
National Bureau of Standards
Washington 25, D.C.
Attn: Division of Mechanics (1)
Engineering Mecha. Sect.(1)
Aircraft Structures (1)

Commandant
U.S. Coat Gurad
1300 E Street, N.W.
Washington 25, D.C.
Attn: Chief, Testing & Devel. Division (1)

U.S. Maritime Administration
General Admin. Office Building
Washington 25, D.C.
Attn: Chief, Div. of Preliminary Design (1)

National Aeronautics & Space Administration
1512 H Street, N.W.
Washington 25, D.C.
Attn: Loads & Structures Div. (2)

Director
Langley Aeronautical Laboratory
Langley Field, Virginia
Attn: Structures (2)

Director
Forest Products Laboratory
Madison, Wisconsin (1)

Civil Aeronautics Administration
Department of Commerce
Washington 25, D.C.
Attn: Chief, Aircraft Engineering Div. (1)
Chief, Airframe & Equipment D (1)

Professor Lynn S. Beedle
Fritz Engineering Laboratory
Lehigh University
Bethlehem, Pennsylvania (1)

Professor R. L. Bisplinghoff
Dept. of Aeronautical Engineering
Massachusetts Inst. of Technology
Cambridge 39, Massachusetts (1)

Professor H. H Bleich
Department of Civil Engineering
Columbia University
New York 27, New York

Professor B. A. Boley
Department of Civil Engineering
Columbia University
New York 27, New York

National Sciences Foundation
1520 H Street, N.W.
Washington, D.C.
Attn: Engineering Sciences Division(1)

Professor G. F. Carrier
Pierce Hall
Harvard University
Cambridge 38, Massachusetts

National Academy of Sciences
2101 Constitution Avenue
Washington 25, D.C.
Attn: Tech. Director, Comm. on Ships' Structural Design
Exec. Sec'ty, Comm. on Undersea Warfare (1)

Professor Herbert Deresciewicz
Dept. of Civil Engineering
Columbia University
632 W. 125th Street
New York 27, New York (1)

Professor D.C. Drucker, Chairman
Divison of Engineering
Brown University
Providence, Rhode Island (1)

Professor A.C. Eringen
Dept. of Aeronautical Engineering
Purdue University
Lafayette, Indiana (1)

Professor W. Flugge
Dept. of Mechanical Engineering
Stanford University
Stanford, California (1)

Professor J. N. Goodier
Dept. of Mechanical Engineering
Stanford University
Stanford, California (1)

Professor L.E. Goodman
Engineering Experiment Station
University of Minnesota
Minneapolis, Minnesota (1)

Professor M. Hetenyi
The Technological Institute
Northwestern University
Evanston, Illinois (1)

Professor P.G. Hodge, Jr.
Dept. of Mechanics
Technology Center
Illinois Inst. of Technology
Chicago 16, Illinois (1)

Professor N.J. Hoff, Head
Division of Aeronautical Engrg.
Stanford University
Stanford, California (1)

Professor W.H. Hoppmann, II
Dept. of Mechanics
Rensselaer Polytechnic Inst.
Troy, New York (1)

Professor Bruce G. Johnston
University of Michigan
Ann Arbor, Michigan (1)

Professor J. Kempner
Dept. of Aerospace Engrg. and Applied Mechanics
Polytechnic Institute of B'klyn.
333 Jay Street
Brooklyn 1, New York (1)

Professor H.L. Langhaar
Dept. of Theoretical and Appl. Mech.
University of Illinois
Urbana, Illinois (1)

Professor B.J. Lazan, Director
Engineering Experiment Station
University of Minnesota
Minneapolis 14, Minnesota (1)

Professor E.H. Lee
Division of Applied Mathematics
Brown University
Providence 12, Rhode Island (1)

Professor George H. Lee
Director of Research
Rensselaer Polytechnic Institute
Troy, New York (1)

Mr. M.M. Lemcoe
Southwest Research Institute
8500 Culebra Road
San Antonio 6, Texas (1)

Professor Paul Lieber
Geology Department
University of California
Berkeley 4, California (1)

Professor R.D. Mindlin
Dept. of Civil Engineering
Columbia University
632 W. 125th Street
New York 27, New York (1)

Professor Paul M. Naghdi
Building T-7
College of Engineering
University of California
Berkeley 4, California (1)

Professor William A. Nash
Dept. of Engineering Mechanics
University of Florida
Gainesville, Florida (1)

Professor N.M. Newmark, Head
Dept. of Civil Engineering
University of Illinois
Urbana, Illinois (1)

Professor Aris Phillips
Dept. of Civil Engineering
15 Prospect Street
Yale University
New Haven, Connecticut (1)

Professor W. Prager, Chairman
Physical Sciences Council
Brown University
Providence 12, Rhode Island (1)

Professor E. Reissner
Dept. of Mathematics
Massachusetts Inst. of Technology
Cambridge 39, Massachusetts (1)

Professor M.A. Sadowsky
Dept. of Mechanics
Rensselaer Polytechnic Institute
Troy, New York (1)

Professor J. Stallmeyer
Dept of Civil Engineering
University of Illinois
Urbana, Illinois (1)

Professor Eli Sternberg
Dept. of Mechanics
Brown University
Providence 12, Rhode Island (1)

Professor S.P. Timoshenko
School of Engineering
Stanford University
Stanford, California (1)

Professor A.S. Velestos
Dept. of Civil Engineering
University of Illinois
Urbana, Illinois (1)

Professor Dana Young
Yale University
New Haven, Connecticut (1)

Dr. John F. Brahtz
Dept. of Engineering
University of California
Los Angeles, California (1)

Mr. Martin Goland, Vice President
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas (1)

Mr. S. Levy
General Electric Research Lab.
6901 Elmwood Avenue
Philadelphia 42, Pa. (1)

Professor B. Budiansky
Dept. of Mechanical Engineering
School of Applied Sciences
Harvard University
Cambridge 38, Massachusetts (1)

Professor H. Kolsky
Division of Engineering
Brown University
Providence 12, Rhode Island (1)

Professor E. Orowan
Department of Mechanical Engrg.
Mass. Institute of Technology
Cambridge 39, Massachusetts (1)

Professor J. Ericksen
Mechanical Engrg. Department
John Hopkins University
Baltimore 18, Maryland (1)

Professor T.Y. Thomas
Graduate Institute for Mathematics and Mechanics
Indiana University
Bloomington, Indiana (1)

Professor Joseph Martin, Head
Dept. of Engineering Mechanics
College of Engrg. and Architecture
Pennsylvania State University
University Park, Pennsylvania (1)

Mr. K.H. Koopman, Secretary
Welding Research Council of
The Engineering Foundation
29 West 39th Street
New York 18, New York (2)

Professor Walter T. Daniels
School of Engrg. and Architecture
Howard University
Washington 1, D.C. (1)

Dr. D.O. Brush
Structures Department 53-13
Lockheed Aircraft Corporation
Missile Systems Division
Synnyvale, California (1)

Professor Nicholas Perrone
Engineering Science Dept.
Pratt Institute
Brooklyn 5, New York (1)

Legislative Reference Service
Library of Congress
Washington 25, D.C.
Attn: Dr. E. Wenk (1)

Commander
Wright Air Development Center
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: Dynamics Branch (1)
Aircraft Laboratory (1)
WCISY (1)

Commanding Officer
USNNOEU
Kirtland Air Force Base
Albuquerque, New Mexico
Attn: Code 20 (Dr. J.N. Brennan) (1)

Professor J.E. Cermak
Dept. of Civil Engineering
Colorado State University
Fort Collins, Colorado (1)

Professor W.J. Hall
Dept. of Civil Engineering
University of Illinois
Urbana, Illinois (1)

Project Staff (10)

For your future distribution (10